

TECHNICAL DATA SHEET

NowoFacade Primer

Product description

NowoFacade Primer restores the material's strength and provides the essential adhesion properties for the subsequent treatment. Prevents cracking and frost damage while offering lasting protection against moisture and water penetrating the material.

Application

For restoring and improving porous mineral surfaces. NowoFacade Primer should be applied to a clean and dry surface - it is important to ensure that the surface is completely dry. Glass or plastic windows should be properly covered during treatment.

Highlights & Features

- Strong water repellent properties
- Highly flexible paint film with excellent flow properties
- Permeable
- Less spray dust

Recommendation

Important! Remember to stir the primer thoroughly and always perform a test coat on a small area to ensure compatibility of the product and the surface being treated.

Technical data

Colour:	After drying, NowoFacade Primer is colourless
Drying time:	At 20°C and a relative humidity of 65%, NowoFacade Primer is touch-dry for re-treatment in approximately 2 hours, depending on the substrate's absorbency and the applied layer thickness
Recoating time:	After approx. 2 hours (at 20°C / 65% RH), you can repaint within a maximum of 24 hours
Coverage capacity:	4-5m ² /ltr depending on the absorbency of the substrate
Application:	Brush, paint roller or with airless spraying equipment
Dilution:	The product must be used undiluted
Cleaning:	Soap and water
Packaging:	25 ltr. canister
Shelf life:	24 months in original sealed packaging
Storage:	Dry, frost-free and out of reach of children
Disposal:	Dispose of contents/container in accordance with local waste regulations

Download the latest safety data sheet at
www.nowocoat.com for more information



COATING THE FUTURE



This Technical Data Sheet (TDS) has been compiled on the basis of our many years of experience and latest know-how in the field. It is the intention to support craftsmen in choosing the right materials and using them according to the regulations. The information contained in this TDS does not constitute a guarantee and does not exempt users from the responsibility to check the material and its suitability for the intended use. All new versions replace previous TDS versions. Last updated 10.10.2024

COATING THE FUTURE

